86th St. 8600 N OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER 800 SECTION 22 TOWNSHIP --5-2-02-IFF: Wilcoxen PARTY CHIEF: ____ Rd CREW: _ TYPE OF MARKER: Harrison Oaklandon METHOD OF ESTABLISHMENT: ____County: 1-2-97 IN. S.P.C. E ZONE NAD '83 NAME: 17052201 N: 517878.1080(m) E: 75165.4050(m) -00-00-00 86th St. 8600 N 64.54 PWP 3.

Original post set 1821 by Laughlin with witnesses: 12" buckeye S 65 W 13 links; 8" elm N 74 E 18 links. Legal by Smith 5-1866 per Lawrence Book pg. 7 called corner 'D' notes that a stone monumented the corner. No witnesses. Legal by Voorhis 6-1869 per Lawrence Township Legal Survey Book pg. 11. called corner 'A' and notes 'set rock' witness were: 20" beech S 77 1/2 W 32 links and 12" elm S 43 E 27 1/2 links. Legal by Voorhis 10-1874 per Lawrence Township Legal Survey Book pg. 35 called corner 'G' and notes 'fd rock set by different surveyors. Murphy per Cripe Job#7428 called stone. 10" dn. 6-18-75 Fortner reflect the 6-74 Cripe ties. Excavated 6-10-82 per Wilcoxen. 2'x2' hole dug 20# elongated stone fd vertically about 1' dn. Harrison set. Re-tied 1-2-97. Re-tied 5-2-02 by Wilcoxen.

REF.	DISTANCE	DESCRIPTION
1.	16.58	Mag nail w/brass washer top wooden handrail S-end
2.	15.91'	Mag nail w/brass washer Top 8" by 13" wooden post
3.	35.59'	Cut 'x' w-edge of manhole
4.	64.54	PK nail N PwP#24-221 FA
5.	26.10	PK nail S PwP#25-221 FA